


The flexible thermocouple extensions illustrated below are constructed using thermocouple wire or thermocouple extension wire. They are used as extension cords to provide suitable connections between sensors, jack panels, or instrumentation.



ORDER CODES

Example Order Number:

JE6, CC - F1B036 - 4, CC

1 Terminations and Options

CODE	DESCRIPTION
JE1	2" split leads with compensated spade lugs
JE2	2" split leads, 1/4" stripped
JE3	2" split leads with spade lugs
JE4	Standard plug
JE5	Standard jack
JE6	Miniature plug
JE7	Miniature jack
JE8	2" split leads with 1/4" female disconnects
For type E, K, or T thermocouples, replace J in order code with required letter designation.	
Options	
BX	Box connector
CC	Cable clamp
CG	Cord Grip (1/2" PVC)
MC	Mating connector
RB	Rubber boot
SP	Solid pin plug

2 Extension Leadwire "B" + "C" Dimension

CODE ^[1]	DESCRIPTION
F1 _ _ _	Fiberglass insulation - solid conductor
F1A _ _ _	Fiberglass insulation - solid conductor - flexible armor
F1B _ _ _	Fiberglass insulation - solid conductor - stainless steel overbraid
F3 _ _ _	Fiberglass insulation - stranded conductor
F3A _ _ _	Fiberglass insulation - stranded conductor - flexible armor
F3B _ _ _	Fiberglass insulation - stranded conductor - stainless steel overbraid
T1 _ _ _	Fluoropolymer insulation - solid conductor
T1A _ _ _	Fluoropolymer insulation - solid conductor - flexible armor
T3 _ _ _	Fluoropolymer insulation - stranded conductor
T3A _ _ _	Fluoropolymer insulation - stranded conductor - flexible armor
C3 _ _ _	PVC insulated - stranded conductor - coil cord (only available in 60" and 120" extended lengths)
[1] Insert 3 digit "B" length in inches. EX: F1036=36" "B" length; for assemblies requiring other than the standard 6" "C" dimension, insert 3 digit "C" length in inches after "B" dimension. EX: F1A036-012=36" "B" length with additional 12" "C" length. For PVC-coated or FEP coated flex, substitute suffix code A with P for PVC and T for FEP coating. Example: F3P is stranded fiberglass leads with PVC flex.	

3 Terminations and Options

CODE	DESCRIPTION
0	No termination
1	2" split leads with compensated spade lugs
2	2" split leads, 1/4" stripped
3	2" split leads with spade lugs
4	Standard plug
5	Standard jack
6	Miniature plug
7	Miniature jack
8	2" split leads with 1/4" female disconnect lugs
Options	
BX	Box connector
CC	Cable clamp
CG	Cord Grip (1/2" PVC)
MC	Mating connector
RB	Rubber boot
SP	Solid pin plug